

Continuous monitoring of WiFi and Mobile telephone networks

A permanent monitoring system that allows on-going scrutiny of the emission levels of any source of electromagnetic radiation (mobile telephone antennas, WiFi, high-voltage power lines, etc.) and verification that they meet the safety standards established by the competent authorities and regulations in each country. The measurements taken can be published via the Internet to the different stakeholder communities.



Compliance with ITU K.83



CONTINUOUS MONITORING (24/365)

of electromagnetic fields in specific or sensitive locations.

SINGLE DEVICE

that is compact, lightweight and durable for outdoor or indoor measurement.

EFFICIENT COMMUNICATION

of measurement data via the Internet to the system's web platform.

ALARM SYSTEM


to provide warnings in real time if radiation levels exceed limits.



cMonitEM

mobile

Monitoring of EMF radiation from mobile telephone antennas.



cMonitEM

WiFi

Monitoring of radiation generated by WiFi communications.

cMONITEM Applications. Measurement of EMF radiation in:



Industry



Telecommunications



Powerline



Defense



Medical

HOW DOES IT WORK?



Emission Source



cMonitEM



Online Control Centre



Technical specifications

Sensor type	Isotropic, true RMS	Isotropic, true RMS
CMonitEM - Mobile	Frequency band: GSM, UMTS, LTE	2.4 GHz
Measurement range	0.04 - 65 V/m (RMS)	0.04 - 65 V/m (RMS)
Dynamic range	> 64 dB	> 64 dB
Sensitivity	0.04 V/m	0.04 V/m
Resolution	0.07 dB	0.07 dB
Interband attenuation	> 30 dB (1100 MHz) > 5 dB (2300 MHz)	> 28 dB GSM900 GSM1800 - 3G
Linearity	< ± 0.4 dB (0.2 - 50 V/m)	< ± 0.4 dB (0.2 - 50 V/m)
Isotropic deviation	< ± 1.7 dB	< ± 1.7 dB
Temperature response	± 0.6 dB (- 20 °C to 60 °C)	
Operational mode	Online/Offline (Data download via USB)	
Communication with Control Centre	GPRS (online mode)	
Memory	Micro SD + Eeprom (1 Gbyte > 1 year)	
Sampling frequency	Every 500 ms	
Power supply	12 Volt DC – AC/DC transformer included	
Operating temperature	- 25 °C to + 60 °C with temperature recording	
Environmental protection	IP 66	
Installation	Wall, mast or flat surface. Can be installed on other equipment (traffic lights)	
Dimensions	157 mm x 178 mm x 133 mm	

Control centre

Allows automatic creation of reports on EMF levels.

Administration web page for remote system management.

Public web page to display measurements on any computer with Internet connection.

Multilingual interface.

Programmable system alarms.

Additional services

Hosted Control Centre:

Eliminate infrastructure and server costs by using Wavecontrol's cloud server.

Warranty extension:

The 2-year standard warranty can be extended to 3, 4 or 5 years.

Calibration plans:

Plan future calibrations now for 24 and 48 months with further discounts.

Update plans:

Keep the system up to date with the latest firmware versions and software development.

Training courses:

EMF theory and practical sessions at Wavecontrol or the client's offices.

Product specifications and descriptions in this document subject to change without notice